



ETA-Danmark A/S
Göteborg Plads 1
DK-2150 Nordhavn
Tel. +45 72 24 59 00
Internet www.etadanmark.dk

Authorised and notified according
to Article 29 of the Regulation (EU)
No 305/2011 of the European
Parliament and of the Council of 9
March 2011

MEMBER OF EOTA



European Technical Assessment ETA-23/0508 of 2025/09/17

I General Part

Technical Assessment Body issuing the ETA and designated according to Article 29 of the Regulation (EU) No 305/2011: ETA-Danmark A/S

Trade name of the construction product:

PULSA HC6 and PULSA UP6 Nails

Product family to which the above construction product belongs:

Power-actuated fastener for multiple use in concrete for non-structural applications

Manufacturer:

SPIT
Route de Lyon
FR-26500 Bourg-Les-Valence
Internet www.spit.com

Manufacturing plant:

SPIT
Route de Lyon
FR-26500 Bourg-Les-Valence

This European Technical Assessment contains:

11 pages including 6 annexes which form an integral part of the document

This European Technical Assessment is issued in accordance with Regulation (EU) No 305/2011, on the basis of:

EAD 330083-03-0601 - Power-actuated fastener in concrete for redundant non-structural applications

This version replaces:

The ETA with the same number issued on 2023-08-21

Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and should be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full (except the confidential Annexes referred to above). However, partial reproduction may be made, with the written consent of the issuing Technical Assessment Body. Any partial reproduction has to be identified as such.

II SPECIFIC PART OF THE EUROPEAN TECHNICAL ASSESSMENT

1 Technical description of product

PULSA HC6 Nails are power-actuated fasteners which are placed into the concrete without previous drill by use of a gas actuated tool PULSA P65, P40P+ or P27.

PULSA UP6 Nails are power-actuated fasteners which guarantee a high success rate of successful fixings in hard materials. They are placed into the concrete without previous drill by use of a gas actuated tool PULSA P65, P40P+.

The nails are anchored in the concrete by sintering and mechanical interlock.

The fastener (nail) is made of galvanised steel. The nails are arranged and connected with each other by special plastic strips that guides the nails in the gas actuated tool magazine

The product specification is given in annex A.

The characteristic material values, dimensions and tolerances of the fastener not indicated in Annexes shall correspond to the respective values laid down in the technical documentation¹ of this European Technical Assessment.

2 Specification of the intended use(s) in accordance with the applicable European Assessment Document (hereinafter EAD)

The HC6 and UP6 Nails are for redundant application in cracked and non cracked normal weight concrete between classes C20/25 and C50/60.

The intended use of the HC6 and UP6 Nails is for indoor conditions in building construction with a maximum thickness of the construction member of 250 mm.

The HC6 and UP6 Nails are type 4 fasteners according to the classification given in EAD 330083-03-0601 with a minimum embedment depth of 13 mm for HC6 and 12,5 mm for UP6.

The performances given in Section 3 are only valid if the anchor is used in compliance with the specifications and conditions given in Annex B.

The provisions made in this European Technical Assessment are based on an assumed intended working life of the fastener of 50 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer or Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

¹ The technical documentation of this European Technical Assessment is deposited at ETA-Danmark and, as far as relevant for the tasks of the Notified bodies involved in the attestation of conformity procedure, is handed over to the notified bodies.

3 Performance of the product and references to the methods used for its assessment

3.1 Characteristics of product

Mechanical resistance and stability (BWR 1):

Characteristic values of resistance: See annex B2 and C1.

Displacements: See annex C1

Safety in case of fire (BWR 2):

Reaction to fire: Class A1

Resistance to fire: See Annex C1.

Durability

See annex B1

3.2 Methods of assessment

The assessment of fitness of the fastener for the intended use in relation to the requirements for mechanical resistance and stability and safety in use in the sense of the Basic Requirements 1 and 2 has been made in accordance with EOTA EAD 330083-03-0601.

4 Assessment and verification of constancy of performance (hereinafter AVCP) system applied, with reference to its legal base

4.1 AVCP system

According to the decision 1997/463/EC of the European Commission, the system(s) of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No 305/2011) is 2+.

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at ETA-Danmark prior to CE marking.

Issued in Copenhagen on 2025-09-17 by



Thomas Bruun
Managing Director, ETA-Danmark

System

Nail designation	Tool P27	Tool P40P+	Tool P65
HC6-17	✓	✓	✓
HC6-22	✓	✓	✓
UP6-17		✓	✓
UP6-22		✓	✓

Nail Types

SPIT HC6-17
SPIT HC6-22



SPIT UP6-17
SPIT UP6-22




Trade name : SPIT HC6 or SPIT UP6

Designation : HC6-LT or UP6-LT with LT : Total length of the nail
 Example : HC6-17 / HC6-22 / UP6-17 / UP6-22

Marking : "S" Identifying mark of the producer on the head

Marking

**SPIT PULSA Gas actuated tool and gas can**

PULSA P27 (95 joules)



PULSA P40P+ (100 joules)



PULSA P65 (100 joules)



The P27, P40P+ and P65 tools must be used with pin guide "P", usually used for drywall application.



Gas can supplies with nails pack



SPIT HC6, UP6
with PULSA P27, PULSA P40 P+ and PULSA P65
Power actuated drywall fasteners

Product description

Annex A1

SPIT HC6**SPIT UP6****Table A1 : Dimensions and materials**

HC6 dimensions			HC6-17	HC6-22	UP6-17	UP6-22
Length	LT	[mm]	17	22	17	22
Shaft diameter	d	[mm]	3,0		3,8	
Effective anchorage depth	h _{ef}	[mm]	≥ 13,0		≥ 12,5	
Head diameter	D	[mm]	6,4		6,4	
Material collated strip		[-]	Polypropylene, orange color		Polypropylene, blue color	
Material nail		[-]	Steel, Hardness ≥ 56 HRc			
Zinc plating		[-]	Mechanical zinc plating, min. zinc 10µm			

SPIT HC6, UP6
with PULSA P27, PULSA P40 P+ and PULSA P65
Power actuated drywall fasteners

Material, dimensions

Annex A2

Specification of intended use**Anchorage subject to :**

- Shear dead loads of drywalls tracks acting on the fastener
- The fasteners HC6-17, HC6-22, UP6-17 and UP6-22 are to be used for fastening metal tracks with a thickness of $0,6 \text{ mm} \leq t \leq 2,0 \text{ mm}$ and a tensile strength of $R_m \geq 260 \text{ N/mm}^2$

	HC6	UP6
▪ Static and quasi-static loads	✓	✓
▪ Fire exposure	✓	

Base materials :

- Reinforced or unreinforced normal weight concrete according to EN 206-1:2000
- Strength classes C20/25 to C50/60 according to EN 206-1
- Cracked and non-cracked concrete
- Anchorages in two-dimensional load-bearing structures (slab and walls)

Use conditions (Environment conditions):

- Structures subject to dry internal conditions

Design :

- Number of fixing points $n_1 \geq 5$,
- Number of fasteners per fixing point $n_2 = 1$,
- Design value of actions $V_{ED,lim}$ per fixing point $\leq 0,6 \text{ kN}$.
- Design concept : $H \cdot s \leq \frac{V_{Rk}}{\gamma_M \cdot \gamma_F}$

With H : Horizontal load per meter acting on the drywall track
 S : Spacing of the fasteners in meter
 V_{Rk} : Characteristic shear load according to Annex C1
 γ_M : Partial safety factor for fastener resistance
 γ_F : Partial safety factor for acting loads


Installation:

- Fastener installation carried out by appropriately qualified personnel and under the supervision of the person responsible for technical matters of the site.
- Use of the fastener only as supplied by the manufacturer without exchanging the components of an fastener.
- Fastener installation in accordance with the manufacturer's specifications and drawings and using the appropriate tools.
- Effective anchorage depth, edge distances and spacing not less than the specified values without minus tolerances
- Effective anchorage depth, edge distances and spacing not less than the specified values without minus tolerances.

SPIT HC6, UP6
with PULSA P27, PULSA P40 P+ and PULSA P65
Power actuated drywall fasteners

Annex B1

Intended use - Specifications

Installed condition

h_{ef} : Effective anchorage depth
 t_{fix} : Thickness of part to be fixed
 h_{min} : Minimum member thickness

Installation parameters

Nail dimensions			HC6-17	HC6-22	UP6-17	UP6-22
Maximum concrete strength class	[-]		C50/60			
Power setting	[-]		DOD MIN / MAX		DOD MAX	
Effective anchorage depth	$h_{ef,k}$	[mm]	$\geq 13,0$		$\geq 12,5$	
Minimum thickness of fixture	Min t_{fix}	[mm]	0,6			
Maximum thickness of fixture	Max t_{fix}	[mm]	2,0			
Minimum member thickness	h_{min}	[mm]	80			
Minimum spacing	S_{min}	[mm]	200			
Minimum edge distance	C_{min}	[mm]	150			

SPIT HC6, UP6
with PULSA P27, PULSA P40 P+ and PULSA P65
Power actuated drywall fasteners

Installation instruction

Annex B2

Installation instructions

▪ With PULSA tool, fuel injection is carried out by an electro valve and an electronic chip (fully automatic tool). PULSA is powered by easily replaceable fuel cells. Each time the nose of the tool is depressed, a metered amount of air and fuel gas mixture is injected into the combustion chamber where it is ignited by a spark when the trigger is pressed. The piston is forced down, driving the fastener to a pre-set depth.

2 conditions to obtain percussion in order :

- Step 1 : Press the tool against the working surface
- Step 2 : Press the trigger

▪ Fasteners to be installed perpendicular to the surface of the base material, by using the SPIT PULSA tool.

▪ When setting, pay attention to setting defects. A setting defect is present if the nail can be pull out of the concrete by hand

▪ Fasteners to be installed ensuring not less than the minimum effective anchorage depth according to table A2. If the embedment depth is smaller than the minimum effective anchorage depth the nail must be assumed as a setting defect and may not be loaded.

▪ A new fastener is set at a minimum distance away of 100 mm of the edge of the damaged surface.

**SPIT HC6, UP6
with PULSA P27, PULSA P40 P+ and PULSA P65
Power actuated drywall fasteners**

Annex B3

Installation instruction

Table C1: Characteristic values

Nail dimensions			HC6-17	HC6-22	UP6-17	UP6-22
For use with tool			P27 P40P+ P65		P40P+ P65	
Characteristic shear strength	V _{Rk}	[kN]	0,56		0,48	
Partial safety factor	γ _M ¹⁾	[-]	1,5			
Minimum spacing	S _{min}	[mm]	200			
Minimum edge distance	C _{min}	[mm]	150			
Displacement for all load directions	δ ₀ , δ _∞	[mm]	≤ 0,1			
1) In absence of other national regulations						

Table C2: Characteristic values under fire exposure

HC6 dimensions				HC6-17	HC6-22
For use with tool				P27 P40P+ P65	P27 P40P+ P65
Characteristic resistance for all directions, for minimum 3 nails per meter length	R30	F _{Rk,fi,30}	[kN/ml]	0,268	
	R60	F _{Rk,fi,60}	[kN/ml]	0,198	
	R90	F _{Rk,fi,90}	[kN/ml]	0,129	
	R120	F _{Rk,fi,120}	[kN/ml]	0,095	
Partial safety factor		γ _{M,fi} ¹⁾	[-]	1,0	
Minimum spacing		S _{min}	[mm]	200	
Minimum edge distance		C _{min} ²⁾	[mm]	150	
1) In absence of other national regulations					
2) If the fire attack is from more than one side, the edge distance shall be c ≥ 300 mm					

SPIT HC6, UP6
with PULSA P27, PULSA P40 P+ and PULSA P65
Power actuated drywall fasteners

Performances

Annex C1